

		<p>3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p>PRODUCT SALES SHEET: Rail Zip 2</p>
---	---	--

Pacer Technology Hobby Rail-Zip 2 (PT-23) is used as a track cleaner and corrosion inhibitor. This high tech concentrated formula cleans, -restores electrical conductivity and eliminates "sparking".

PROPERTIES: Appearance – red liquid with mild odor.

USE INSTRUCTIONS: FOR PROFESSIONAL USE ONLY. Read all directions and cautions before use.

Remove cap and apply Rail-Zip to clean cloth, cotton swab, felt pad or sponge. Apply directly to surface area to be treated. A thin, uniform coating is best. Do not rub Rail-Zip. Product works chemically, not mechanically. Allow product to work overnight (10-12 hours) to penetrate and protect. Optional: Remove any excess residue by wiping lightly with clean cloth lightly moistened with water.

STORAGE AND SHELF LIFE: Recap for storage. A one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS:

WARNING: HARMFUL. MAY CAUSE CANCER. IRRITATING TO SKIN & EYES. USE IN WELL-VENTILATED AREA. Overexposure to chemical may cause headache, drowsiness, respiratory and skin irritation, nausea and numbness. Contains Hydrotreated Light Naphthenic Petroleum Distillates.

First Aid: In case of accident or if you feel unwell, seek medical advice immediately and show container label. **Eyes:** With eyelids open, flush with water for 15 minutes and seek medical attention. **Skin:** Wash with soap & water and seek medical attention if irritation persists. **Inhalation:** Remove to fresh air & seek medical advice. **Ingestion:** Do not induce vomiting. If vomiting occurs, keep head below hips to avoid aspiration of vomitus into lungs. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.**

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com and click on the ZAP logo. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 3 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.