

		<p>3281 - Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com</p> <p>Model/Hobby Cement</p>
---	---	---

Pacer Technology Super Glue Model/Hobby Cement (15263) is a single component polystyrene resin adhesive that remains clear after cure and is best used for:

- Wood
- Plastic
- Polystyrene models
- Toys
- Cardboard
- Ceramics

PROPERTIES:

Initial color: Clear

Final color: Clear

Tack-free time: Less than 5 minutes

Full Strength: 24 hours

Operating Temperature Range: 30⁰ to 135⁰F
(-1⁰ to 57⁰C)

Note: This product works by attacking the plastic surface and welding the parts together. DO NOT USE ON ANY AREA THAT DOES NOT REQUIRE BONDING. **Not recommended for bonding Styrofoam materials.**

USE INSTRUCTIONS: Use in well-ventilated area.

1. Surfaces should be clean and dry. For best results, use fine sandpaper to roughen surface.
2. For small repairs, apply directly from tube to one surface and press edges together or clamp until set. For large area repairs, apply thin coat to both surfaces.
3. For optimum strength in all applications, wait 24 hours before using repaired object.

Note: Avoid glue smudges on models and spilling of product on rugs, furniture, etc.

STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains methyl ethyl ketone. – WARNING – Flammable. Vapor Harmful. Harmful if swallowed. Injurious to eyes. Avoid contact with eyes, mucous membranes and prolonged skin contact. Use & store in well-ventilated area away from heat or flame. In case of eye contact, flush with water for 15 minutes & get medical attention. For skin contact, wash well with soap and water. If irritation persists, get medical attention. If swallowed, do not include vomiting, get immediate medical attention and show container label.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com . In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.