

		3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800)538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com
PRODUCT DATA SHEET		SUPER WEATHERSTRIP

Page 1 of 2

Pacer Technology's Pro Seal® **SUPER WEATHERSTRIP AND GASKET ADHESIVE** is a versatile, flexible product designed for use in automotive and household repair of vinyl, plastic, rubber, metal and wood products.

PROPERTIES:

LIQUID STATE

Base Chemical	Synthetic rubber and resin suspen (Acetone, hexane, toluene and methyl ethyl ketone)
Flashpoint, (TCC)	<0°F (<-18°C)
Weight per Gallon	Approximately 7.3 lbs @ 75 °F (24°C)
Color	Yellow
Viscosity, cps (RVF, #4, 20rpm)	Nominal 4000 @ 75 °F (24°C)
VOC	3.76 lb/gal
Boiling Point, °F (°C)	133 °F (56 °C)

CURED STATE

Tack Time	3 to 30 minutes
Fluid Resistance	High resistance to heat & moisture. Good oil resistance.
Temperature Limit	325 °F (163 °C)
Soluble In:	Acetone, toluene.

APPLICATION INSTRUCTIONS

For best results, parts should be clean and free from oil, grease, rust and dirt. Apply sufficient amount of product to one surface, press together to transfer adhesive and separate parts. Let dry until tacky, then press firmly together. Adhesive will achieve 90% of full strength in 24 hours.

Contact Adhesive – Special Purpose: 80% VOC.

For Consumer use only. Not for Industrial or Commercial Applications. Does not comply to Rule 1168 requirements.

STORAGE AND SHELF LIFE

Store product in a cool, dry location. Stored under these conditions, a one-year shelf life can be expected.

		3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800)538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com
PRODUCT DATA SHEET		SUPER WEATHERSTRIP

Page 2 of 2

SAFETY AND HANDLING PRECAUTIONS

Danger: Extremely flammable. Vapors harmful. Harmful or fatal if swallowed. Vapors may cause flash fire or may ignite explosively. Use and store in well-ventilated area away from heat, sparks or open flame. Close container securely after use.

Harmful or fatal if swallowed. Avoid prolonged contact with skin or breathing of vapors. Contains acetone, hexane, toluene and methyl ethyl ketone. If swallowed do not induce vomiting. Call physician immediately and show container label. KEEP OUT OF REACH OF CHILDREN.

WARNING: This product contains chemicals known to the State of California to cause cancer or other reproductive harm.

For more information, refer to Material Safety Data Sheet available upon request.

In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 637-9803 (outside CA only) or (909) 987-0550.

PRODUCT NUMBER: N88881

Rev 3 – 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.