



3281 Guasti Road, Suite 260 Ontario, CA 91761 (909) 987-0550 (800) 538-3091 Fax: (909) 987-0490 http://www.supergluecorp.com

Bondini 2 Brush-On

Pacer Technology Bondini 2 Brush-On (B210) is a quick-setting adhesive that works on oily & dirty surfaces to bond most porous and non-porous materials, such as:

- Metal
 - Leather

Wood

Rubber

Ceramic

Most Plastics Porcelain

NOTE: Not for use with Teflon, polyethylene, polypropylene, certain silicone rubber types, glass, rear view mirrors or parts that are subjected to great shock or continuous immersion in water.

PROPERTIES:

Initial color: Clear, transparent Final color: Clear Set time: 10-30 second

Full Strength: 24 hours Operating Temperature Range: -65⁰ to 180⁰F $(-54^{\circ} \text{ to } 82^{\circ} \text{C})$

USE INSTRUCTIONS: NOTE: For best results, items should fit closely together,

- 1. Protect clothing and work surfaces (metal foil works well). Use in a well-ventilated area. Carefully unscrew cap while keeping bottle pointed away from face.
- 2. Brush apply to one surface. Assemble parts and hold together with pressure for 15 seconds or until set.
- 3. Wipe top of bottle neck if adhesive has accumulated before closing bottle securely after use.

STORAGE AND SHELF LIFE

Store upright in a cool area away from sunlight or heat sources. Stored under these conditions, a oneyear shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS

Contains cyanoacrylate. CAUTION: Eye Irritant. Bonds skin & eyes in seconds. Use with adequate ventilation. Avoid contact with clothing as can cause burn. In case of eye contact, flush with water for 15 minutes; get medical attention for eye or internal contact. To remove from skin, soak in acetone nail polish remover & gently peel adhesive off with fingernail; water exposure will wear off residual adhesive in a few days (do not use polish remover around eye area). KEEP OUT OF REACH OF CHILDREN.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com . In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 3 - 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.