



3281 - Guasti Road, Suite 260 Ontario, CA 91761

(909) 987-0550 (800) 538-3091 Fax: (909) 987-0490

http://www.supergluecorp.com

# **Vinyl/Leather Mender**

Pacer Technology Super Glue Vinyl/Leather Mender (T-VL) is a single component vinyl adhesive that remains clear and flexible after cure and is best used for:

Upholstery

Clothing

Luggage

Vinyl Pools

Vinyl Boots

Rainwear

Boat covers

Air mattresses

## **PROPERTIES:**

<u>Initial color:</u> Clear

<u>Final color:</u> Clear Set Time: 10 minutes to 1 hour Full Strength: 24 hours

Operating Temperature Range: 40° to 150°F

 $(4^{\circ} \text{ to } 66^{\circ}\text{C})$ 

## **USE INSTRUCTIONS:** Use in well-ventilated area.

- 1. Surfaces should be clean and dry. For best results, use fine sandpaper to roughen surface.
- 2. For small repairs, apply directly from tube and press edges together using masking tape and holding for 10 minutes.
- 3. For large repairs, place cloth-backing material underneath the damaged area and bond together. Allow 1 hour for drying.
- 4. For optimum strength in all applications, wait 24 hours before using repaired object.

Note: Not recommended for repairs that will be exposed to prolonged UV or sunlight exposure.

#### STORAGE AND SHELF LIFE

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

### SAFETY AND HANDLING PRECAUTIONS

Contains xylene mixture of isomers, methyl ethyl ketone, tetrahydrofuran, acetone and ethylbenzene. Danger – liquid adhesive is extremely flammable. Harmful or fatal if swallowed. Vapor harmful. Wear suitable protective clothing and gloves. Avoid skin contact & inhalation of vapors. If swallowed, contact physician immediately and show the container label. Wash hands & skin with soap and water after use. KEEP OUT OF REACH OF CHILDREN.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ <a href="www.supergluecorp.com">www.supergluecorp.com</a>. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 1 - 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.